

# **PLEIADES-HR SYSTEM QUALIFICATION: A FOCUS ON GROUND PROCESSING AND IMAGE PRODUCTS PERFORMANCES, A FEW MONTHS BEFORE LAUNCH**

*Simon BAILLARIN, Laurent LEBEGUE, Philippe KUBIK*

CNES (Centre National d'Etudes Spatiales)  
18 avenue Edouard Belin - 31401 TOULOUSE CEDEX 4 – FRANCE  
Simon.Baillarin@cnes.fr

## **1. INTRODUCTION**

PLEIADES-HR is the highest resolution civilian earth observing system ever developed in Europe. This optical imaging project is conducted by the French National Space Agency, CNES. It will operate two agile satellites designed to provide optical images to civilian and defense users. The first satellite will be launched in February 2009, the second 18 months later. Images will be simultaneously acquired in Panchromatic (PA) and Multi-Spectral (XS) modes. It will allow, in Nadir acquisition condition, to deliver 20 km wide, false or natural colored scenes with a 70 cm ground sampling distance (after PA+XS fusion).

Imaging capabilities have been highly optimized in order to acquire, in the same pass, along-track mosaics, stereo pairs and triplets, and multi-targets. To fulfill the operational requirements and ensure quick access to information, ground processing has to automatically perform the radiometric and geometric corrections. Since ground processing capabilities have been taken into account very early in the mission development, it has been possible to relax some costly on-board components requirements, in order to achieve a cost effective on-board/ground compromise.

## **2. FROM SYSTEM TO PRODUCTS DEFINITION**

Starting from the PLEIADES system and on board characteristics (agility, stability, location accuracy...), this paper presents an overview of ground segment functional breakdown and focuses more precisely on the image production processing [1]. A definition of each level of image product (level 1, perfect sensor, ortho-image and ortho-mosaic) is done with the main processing steps. Then it shows how images product performance is a result of the satellite performance followed by an appropriate ground processing (radiometric and geometric processing).

## **3. SIMPLIFYING THE FOCAL PLANE: A “PERFECT SENSOR” PRODUCT**

The complexity of the PLEIADES focal plane makes the classical level 1 product difficult to use. A new product level called “Perfect Sensor” or more simply “Sensor Level” had been proposed [2].

This “Sensor Level” is described: a basic product specially designed for the photogrammetric community and delivered with a physical model and a rational function model. The high geometric accuracy of the rational function model is assessed and compared to the physical model.

## **4. ORTHORECTIFIED PRODUCTS PERFORMANCES**

The automatic “ortho-image” and “ortho-mosaic” production process is also described.

PLEIADES-HR ortho-mosaic product will provide end-users with an image of larger size, as being the result of a seamless ortho-rectified patchwork of individual strips. The output coverage may reach up to 10000 km<sup>2</sup> and even more, according to the length of the neighboring strips and the tolerated stereo effect between acquisitions.

This product represents the successful realization of the PLEIADES mission since it takes advantage of the main characteristics of the system: agility and high location precision. The automatic mosaicking process relies on automatic tie point selection [3] & [4] and geometric models refining phases followed by local radiometric corrections and stitching phases.

The geometric accuracy and the overall radiometric quality are evaluated from simulated Pleiades acquisitions (aerial images) and the excellent results obtained are presented.

## **5. CONCLUSION AND OUTLOOK**

Finally the paper presents the ground segment architecture dimensioned to handle this “heavy” processing. It describes the associated configuration set-up in CNES, Spot-Image and Defenses premises for the in-progress qualification phases, a few months before satellite launch.

## **7. REFERENCES**

- [1] P.Kubik, V. Pascal, C. Latry, S. Baillarin “PLEIADES image quality: from users’ needs to products definition”, SPIE Europe, Brugges (Belgium), 2005
- [2] F. De Lussy, P. Kubik, D. Greslou, P. Gigord “Pleiades-HR image system products and geometric accuracy”, ISPRS, Hanover (Germany), 2006
- [3] S. Baillarin, M. Bernard, M. Chikhi “High Location Accuracy Allows Reference3D™ supporting Versatile and Innovative Services”, ISPRS, Goa (India), 2006
- [4] S. Baillarin, J.P. Gleyzes, C. Latry, Breton E., Bouillon A., L. Cunin, C Vesco, JM Delvit “Validation of an automatic image ortho-rectification processing”, Proceedings IGARSS, Anchorage (USA), 2004